



Portable Gas Monitoring

Dräger

Technology for Life

Pac® Diffusion Single & Dual Gas Monitors

IP 68 Rated | Event Logger | 24 Month Battery

Pac® 6000 - Single Gas (Life limited to 2 yrs)



CO
 PN: 8326369
 0-2000 ppm
 35 / 50 ppm alarms
 Cal Gas 4594655



H₂S
 PN: 8326368
 0-100 ppm
 10 / 15 ppm alarms
 Cal Gas 4594655




O₂
 PN: 8327612
 0-25 vol %
 19.5 / 23.5 Vol % alarms
 Cal Gas 4594655



SO₂
 PN: 8328273
 0-100 ppm
 0.5 / 1 ppm alarms
 Cal Gas 4594961

Pac® 6500 - Single Gas



CO
 PN: 8327614
 0-2,000 ppm
 35 / 50 ppm alarms
 Cal Gas 4594655



H₂S
 PN: 8327613
 0-100 ppm
 10 / 15 ppm alarms
 Cal Gas 4594655



O₂
 PN: 8327616
 0-25 vol %
 19.5 / 23.5 Vol % alarms
 Cal Gas 4594655



SO₂
 PN: 8328274
 0-100 ppm
 0.5 / 1 ppm alarms
 Cal Gas 4594961




Bluetooth capable,
 must be specified at
 time of order


Pac® 8500 - Dual Gas



O₂/CO - LC
 PN: 8328265
 0-25 % Vol O₂
 19.5 / 23.5 Vol% alarms
 0-2000 ppm **CO**
 35 / 50 ppm alarms



H₂S/CO - LC
 PN: 8328263
 0-100 ppm **HS₂**
 0.1 / 0.2 ppm alarms
 0-2000 ppm **CO**
 35 / 50 ppm alarms



CO-H Compensated
 PN: 8327617
 0-2000 ppm
 30 / 50 ppm alarms

Pac® Accessories

Pac® 6x00




Dust Filter Sensor Grill
 PN: 8326853 (4 pcs)
 PN: 8326857 (40 pcs)

* Special Tygon® tubing is required for calibration.
 ** CC Vision is required to program to CLO:

Pac® Diffusion Single Exotic Gas Monitors

IP 68 Rated | Event Logger | 24 Month Battery


Pac® 8000 - Exotic Single Gas



NO₂
 PN: 8326350
 0-50 ppm
 25 / 50 ppm alarms
 Cal Gas 4595193




CO₂
 PN: 8326351
 0-5 Vol %
 0.5 / 1 Vol % alarms
 Cal Gas 4595193




Cl₂ & ClO₂**
 PN: 8326352
 0-20 ppm
 0.5 / 1 ppm alarms
 Cal Gas 4597194*



HCN
 PN: 8328276
 0-50 ppm
 2.5 / 4.5 ppm alarms



NH₃
 PN: 8328277
 0-300 ppm
 25 / 50 ppm alarms*




PH₃
 PN: 8326355
 0-20 ppm
 0.1 / 0.2 ppm alarms




OV
 PN: 8326356
 0-200 ppm
 10 / 20 ppm alarms



OV-A
 PN: 8326357
 0-200 ppm
 10 / 20 ppm alarms



NO₂
 PN: 8328275
 0-50 ppm
 2.5 / 4.5 ppm alarms




Ozone
 PN: 8326359
 0-10 ppm
 0.1 / 0.2 ppm alarms



Battery PN: 8326856

- Interchangeable 3.6V Lithium "AA" battery
- After a battery change, sensor warming time applies.




Water & Dust Filter Sensor Grill
 PN: 8326852 (4 pcs)
 PN: 8326859 (40 pcs)



Comm. Cradle
 PN: 8318587
 For Data, Sensor Swaps, and updates.

NOTE: Free CC Vision download required, scan Software SQ code.



Phosgene
 PN: 8326360
 0-10 ppm
 0.1 / 0.2 ppm alarms

X-am® Single & Multi Gas Monitors

IP 68 Rated | Data/Event logger

X-am® 2800 – Standard 4-gas



CH₄, O₂, CO, H₂S
 PN: NA11350
 This part number includes the battery and charger.
12-16 Hour Battery

X-am® 5800 – Configurable 5-gas



CH₄, O₂, CO, H₂S
 PN: 3703850
12-16 Hour Battery

Pump (PN: 8327115) and charger (PN: 8320333) sold separately

Part No.	Gases
VN 00800	CatEx, H2S/CO-LC, O2
VN 00801	CatEx, H2S/CO-LC, HCN, O2 PR
VN 00802	CatEx, H2S/CO-LC, SO2, O2

X-am® 5100 – Exotic single gas



PN: 8322750
 Base Unit

H₂ O₂ X-am® 5100
 with battery charging set 2.0 - PN VN 000148

H₂ O₂ Sensor only
 PN: 6809170
 – Hydrogen Peroxide

HF/HCl X-am® 5100
 with battery and charging set 2.0 - PN VN 000146

HF/HCl Sensor only
 PN: 6809140

- Hydrogen Chloride
- Hydron Bromide
- Hydrogen Fluoride
- Nitric Acid
- Phosph. Oxychloride
- Phosph. Trichloride

N₂H₄ Sensor only
 PN: 6809190
 – Hydrazine



Calibration Adapter for X-am® 5100
 PN: 6806291 and Regulator 500 ML/min
 PN: 4557020



X-zone® Cover for X-am® 5100
 PN: 8323938

X-am® 8000 – PID/IR/CatEx 7-gas



16-24 Hour Battery

Config.	Part No.	Gases
1	VN 00134	LEL/CatEx, CO/H2S, O2, NH3
2	VN 00135	LEL/Catex, CO/H2S, O2, Cl2
3	VN 00136	PID HC, LEL/CatEx, CO, O2, H2S
4	VN 00137	LEL/CatEx, CO-H2, O2
5	VN 00138	PID HC, LEL/CatEx, CO/H2S, O2
6	VN 00139	PID HC, LEL/IR, O2, H2S, CO
7	VN 00140	PID HC, EX/CO2, CO, O2, HCN
8	VN 00141	LEL/CatEx, H2S/O2, CO, H2
9	VN 00142	PID HC, LEL/CatEx, CO/H2S, O2, HCN
10	VN 00143	PID HC, LEL/CatEx, CO/O2, H2S, CO2
11	VN 00144	LEL/IR, H2-HC, CO
12	VN 00145	PID HC, LEL/CatEx, O2, CO, H2S
13	VN 00401	PID HC, LEL/CatEx, O2, H2S-LC/CO-LC, HCN
14	VN 00483	PID LC ppb, LEL/CatEx, CO-LC, H2S-LC, O2

✱ Bluetooth capable

Selective GC/PID Multi Gas Monitor

IP 54 Rated | Event Logger | 8+ Hour Battery

X-pid® 9500/9500+ – Gas Chromatograph



PID + GC Gas Measurement Device

PN: 6851848

Detects over 60 compounds using a combination of PID + GC technology:

- Acetone
- Benzene
- Butadiene, 1,3-
- Ethanol
- Hexane
- Methyl bromide
- Phosphine
- Toluene
- Vinyl chloride
- Xylene

...and many more

Perimeter Monitoring



X- zone® 5800

PN: 8329040
with integrated pump,
915 MHz, 24 Ah battery
with diffusion and
pump cap

Compatible with:

X-am® 5000

X-am® 5600

X-am® 5100

(diffusion only)



Power Plug

PN: 8320749

(sold separately)



Inductive Charger

Power PN: 8322076

(sold separately)

X-am® Charging Accessories



1-Device Charging Cable

PN: 8316997



5-Device Charging Cable

PN: 8316994



X-am® 8000 Adapter to link chargers

PN: 8325736 +

Power cord

PN: 8321850



X-am® Standard Battery Charge Kit

PN: 8320333



X-am® 8000 Inductive Charger

PN: 8325825

Bump & Calibration X-dock® Station

1 X-dock® Base



6300 Master
(3 gas inlets)
PN: 8321900



6600 Master
(6 gas inlets)
PN: 8321901



**100-240V, 24V DC,
1.25A**
Powers up to 3
modules.
PN: 8321849



**100-240V, 24V DC,
6.25A**
Powers up to 10
modules.
PN: 8321850

3 X-dock® Module



Pac® Module
PN: 8321892



**X-am® 2x00, 5x00
Module**
PN: 8321890



**X-am® 2x00, 5x00
Charging Module+**
PN: 8321891



**X-am® 3500, 8000
Module**
PN: 8321893



**X-am® 3500, 8000
Charging Module+**
PN: 8321894

4 X-dock® Pressure Regulator



Pressure Regulator
PN: 8324250



**Stainless Steel
Pressure Regulator**
for exotic gases
PN: 8324252
**Required for chlorine
& ammonia gases**



**FKM Tubing
(not for Cl₂)**
PN: 4594112 (5 ft)
PN: 4594114 (20 ft)



Tygon® PTFE Lined
PN: 8326980 (9 ft)
Required for chlorine & ammonia gases



PTFE Hose Connector
PN: 8324098

Both required

Accessories

Multi-gas



Float Only
PN: 6802337

Float Probe, 5cm hose+ conn 5mm
PN: 8327654



Water & Dust Filter set with 3mm/5mm hose connectors
PN: 8319364 (1 pcs)
PN: 3705997 (20 pcs)



Telescopic Probe ES 150, 59in
PN: 8316533



Pump adapter for X-am® 3500/8000
PN: 8326820
Includes dust and water filter with Luer connection



Pump for X-am® 2500/ 5000/5600/ 2800/5800
PN: 8327115
Includes USB charger, wall plug and shoulder



X-am® 2x00/5x00 Confined Space Entry Kit
PN: 8327117
Includes pump, usb cable, wall plug, 16' FKM hose, float probe, dust & water filter, shoulder strap, & carry case

Communication



X-am® Communication Cradle
PN: 8318752



USB-IR Com Dongle
PN: 8317409
For Data, Sensor Swaps, and updates.
PN: 8325859 - X-am® 8000 Rubber Boot sold separate

Both required

X-am® Replacement Battery




2500/5000/5600 2800/5800
PN: 3703887




3500/8000
PN: 8326817

Bump Test



Pac® Bump Test Station PN: 8317410



X-am® Bump Test Station PN: 8319131

• Calibration Gas **NOT** included

Sensor Compatibility

Sensor Description	Measuring Range	Accuracy (% of measured volume)	Resolution	Part No.	Pac® 60/6500	Pac® 8000
XS DrägerSensor®						
Hydrazine (N ₂ H ₄) XS N ₂ H ₄ (hydrazine) CH ₃ NH-NH ₂ (monomethyl hydrazine) (CH ₃) ₂ N-NH ₂ (dimethyl hydrazine)	Max 0 - 3.00 ppm 0 - 3.00 ppm 0 - 3.00 ppm 0 - 3.00 ppm	≤ ±5%	0.01 ppm	6809190		
Hydrogen Fluoride/Hydrogen Chloride (HF/HCl) XS HCl (hydrogen chloride) HNO ₃ (nitric acid) HBr (hydrogen bromide) POCl ₃ (phosphorous trichlorideoxide) PCl ₃ (phosphorous trichloride) HF (hydrogen fluoride)	Max 0 - 30.0 ppm 0 - 30.0 ppm 0 - 30.0 ppm 0 - 30.0 ppm 0 - 30.0 ppm 0 - 30.0 ppm 0 - 30.0 ppm	≤ ±15%	0.1 ppm	6809140		
Hydrogen Peroxide (H ₂ O ₂) XS	0 - 20.0 ppm	≤ ±10%	0.1 ppm	6809170		
XXS DrägerSensor®						
Amines XXS CH ₃ NH ₂ (methylamine) (CH ₃) ₂ NH (dimethylamine) CH ₃) ₃ N (trimethylamine) C ₂ H ₅ NH ₂ (ethylamine) (C ₂ H ₅) ₂ NH diethylamine) (C ₂ H ₅) ₃ N (triethylamine)	Std 0 - 100 ppm 0 - 100 ppm 0 - 100 ppm 0 - 100 ppm 0 - 100 ppm 0 - 100 ppm 0 - 100 ppm	≤ ±5%	1 ppm	6812545		
Ammonia (NH ₃) XXS	0 - 300 PPM	≤ ±3%	1 ppm	6810888		■
Carbon Dioxide (CO ₂) XXS	0 - 7.0%	≤ ±20%	0.1% Vol.	6810889		■
Carbon Monoxide (CO) XXS ¹	0 - 2,000 ppm	≤ ±2%	2 ppm	6810882		
Carbon Monoxide Low Conc. (CO) XXS LC ¹	0 - 2,000 ppm	≤ ±2%	1 ppm	6813210	■	
Carbon Monoxide High Conc. (CO) XXS HC	0 - 10,000 ppm	≤ ±2%	5 ppm	6812010		
CO Hydrogen Compensated (CO-H ₂ CP) XXS	0 - 2,000 ppm	≤ ±2%	1 ppm	6811950		
CO-LC/H ₂ S-LC Dual Sensor XXS	0 - 2,000 ppm CO 0 - 100 ppm H ₂ S	H ₂ S: ≤ ± 5 %, CO: ≤ ± 2 %	1 ppm 0.1 ppm	6813280		
CO/H ₂ S Dual Sensor XXS	0 - 2,000 ppm CO 0 - 200 ppm H ₂ S	≤ ±2%	2 ppm 1 ppm	6811410		
Chlorine (Cl ₂) XXS Cl ₂ (chlorine) F ₂ (fluorine) Br ₂ (bromine) ClO ₂ (chlorine dioxide)	Std 0 - 20 ppm 0 - 20 ppm 0 - 20 ppm 0 - 20 ppm 0 - 20 ppm	≤ ±2%	0.1 ppm	6810890		■
Hydrogen Cyanide (HCN) XXS	0 - 50 ppm	≤ ±5%	0.1 ppm	6810887		■
Hydrogen Cyanide (HCN) XXS PC	0 - 50 ppm	≤ ±5%	0.5 ppm	6813165		
Hydrogen High Conc. (H ₂) XXS HC	0 - 4% Vol.	≤ ±2%	0.1% Vol.	6812025		
Hydrogen Low Conc. (H ₂) XXS	0 - 2,000 ppm	≤ ±1%	5 ppm	6812370		
Hydrogen Sulfide High Conc. (H ₂ S) XXS HC	0 - 1,000 ppm	≤ ±2%	2 ppm	6812015		
Hydrogen Sulfide Low Conc. (H ₂ S) XXS LC ¹	0 - 100 ppm	≤ ±2%	0.1 ppm	6811525	■	

Pac® 8500	X-am® 5100	X-am® 2800	X-am® 5800	X-am® 8000	Warranty	Recomm. Cal Interval (months)	Max. Cal Interval (months)	Calibration manually or with CC-Vision	Bump Test or Calibration with X-dock®	Comments*
	■				1-Yr	3	6	DraegerService	N/A	Factory calibration
	■				1-Yr	12 Month	18	10 or 25 ppm HCl	N/A	SS Regulator, PTFE-lined hose (short as possible)
	■				1-Yr	3	6	10 ppm SO ₂	N/A	
			■	■	1-Yr	3	6	50 ppm NH ₃	50 ppm NH ₃	Use Tygon® tubing and Stainless-Steel Regulator
			■	■	1-Yr	3	6	50 ppm NH ₃	50 ppm NH ₃	Use Tygon® tubing and Stainless-Steel Regulator
			■	■	15-Mo	3	6	2.5% Vol CO ₂	2.5% Vol CO ₂	
			■	■	3-Yr	6	12	100 ppm CO	100 ppm CO	
		■	■	■	3-Yr	6	12	100 ppm CO	100 ppm CO	
			■	■	1-Yr	3	6	100 ppm CO	100 ppm CO	
■			■	■	1-Yr	6	12	100 ppm CO 500 ppm H ₂	100 ppm CO 500 ppm H ₂	
■			■	■	2-Yr	6	12	100 ppm CO 25 ppm H ₂ S	100 ppm CO 25 ppm H ₂ S	
				■	2-Yr	6	12	100 ppm CO 25 ppm H ₂ S	100 ppm CO 25 ppm H ₂ S	
			■	■	1-Yr	3	6	5 ppm Cl ₂	5 ppm Cl ₂	Use Stainless-Steel Regulator and PTFE-lined Tygon® tubing with 2ea. 8324098 X-dock® PTFE Hose Connector Sets for connection to X-dock®.
			■	■	2-Yr	3	6	10 ppm HCN	10 ppm HCN	
			■	■	1-Yr	3	6	10 ppm HCN	10 ppm HCN	
			■	■	1-Yr	3	6	2% Vol (50%LEL) H ₂	2% Vol (50%LEL) H ₂	Check on compatibility with CO or CO-H ₂ sensors
			■	■	1-Yr	3	6	500 ppm H ₂	500 ppm H ₂	
			■	■	1-Yr	3	6	100 ppm H ₂ S	100 ppm H ₂ S	
		■	■	■	3-Yr	6	12	25 ppm H ₂ S	25 ppm H ₂ S	

Sensor Description	Measuring Range	Accuracy (% of measured volume)	Resolution	Part No.	Pac® 60/6500	Pac® 8000
Nitrogen Dioxide (NO ₂) XXS	0 - 50 ppm	≤ ±2%	0.1 ppm	6810884		■
Nitrogen Dioxide Low Conc. (NO ₂) XXS LC	0 - 50 ppm	≤ ±3%	0.02 ppm	6812600		■
Nitrogen Oxide (NO) XXS	0 - 200 ppm	≤ ±3%	1 ppm	6811545		■
Odorant (mercaptan) XXS THT (tetrahydrothiophene) (CH ₃) ₃ CSH (tert.-butyl mercaptane) C ₂ H ₅ CH(CH ₃)SH (sec.-butyl mercaptane) CH ₃ SH (methyl mercaptane) C ₂ H ₅ SH (ethyl mercaptane) (CH ₃) ₂ S (dimethyl sulphide) CH ₃ SSCH ₃ (dimethyldisulphid)	Std 0 - 40 ppm 0 - 40 ppm 0 - 40 ppm 0 - 40 ppm 0 - 40 ppm 0 - 40 ppm 0 - 100 ppm 0 - 40 ppm	≤ ±3%	1 ppm	6812535		
Organic Vapor (OV) XXS C ₂ H ₄ O (ethylene oxide) C ₃ H ₆ O (propylene oxide) C ₂ H ₄ (ethene / ethylene) C ₃ H ₆ (propene) C ₂ H ₃ Cl (vinyl chloride) CH ₃ OH (methanol) CH ₂ CHCHCH ₂ (butadiene) HCHO (formaldehyde) (H ₃ C) ₂ CHOH (iso-propanol) C ₄ H ₈ O (tetrahydrofuran) C ₂ H ₃ OCH ₂ Cl (1-chloro-2,3-epoxypropane) C ₆ H ₅ CHCH ₂ (styrene) H ₂ C(CH ₃)COOCH ₃ (methyl methacrylate)	Std 0 - 200 ppm 0 - 200 ppm 0 - 200 ppm 0 - 100 ppm 0 - 100 ppm 0 - 100 ppm 0 - 200 ppm 0 - 100 ppm 0 - 100 ppm 0 - 300 ppm 0 - 200 ppm 0 - 100 ppm 0 - 100 ppm 0 - 100 ppm	≤ ±5%	0.5 ppm	6811530		■
Organic Vapor A (OV-A) XXS C ₂ H ₄ O (ethylene oxide) 2CCHCN (acrylonitrile) (CH ₃) ₂ CCH ₂ (isobutene) CH ₃ COOC ₂ H ₅ (vinylacetate) C ₂ H ₅ OH (ethanol) CH ₃ CHO (acetaldehyde) (C ₂ H ₅) ₂ O (diethyl ether) C ₂ H ₂ (ethine / acetylene)	Std 0 - 200 ppm 0 - 200 ppm 0 - 100 ppm 0 - 300 ppm 0 - 100 ppm 0 - 300 ppm 0 - 200 ppm 0 - 200 ppm 0 - 100 ppm	≤ ±20%	1 ppm	6811535		■
O ₂ /CO-LC Dual Sensor XXS	0 - 25% Vol O ₂ 0 - 2,000 ppm CO	O ₂ : ≤ ± 1%, CO: ≤ ± 2 %	0.1%Vol 1 ppm	6813275		
O ₂ /H ₂ S-LC	0 - 25% Vol O ₂ 0 - 100 ppm H ₂ S	O ₂ : ≤ ± 1%, H ₂ S: ≤ ± 5 %	0.1%Vol 0.1 ppm	6814137		
Oxygen (O ₂) XXS ¹	0 - 25% Vol.	≤ ±1%	0.1% Vol.	6810881		■
Oxygen (O ₂) XXS O2 100	0 - 100% Vol.	≤ ±1%	0.5% Vol.	6812385		
Oxygen (O ₂) XXS PR	0 - 30% Vol.	≤ ±1%	0.1% Vol.	6800530		
Ozone (O ₃) XXS	0 - 10 ppm	≤ ±3%	0.01 ppm	6811540		■
Phosgene (COCl ₂) XXS	0 - 10 ppm	≤ ±5%	0.01 ppm	6812005		■
Phosphine (PH ₃) XXS PH ₃ (phosphine) AsH ₃ (arsine) B ₂ H ₆ (diborane) SiH ₄ (silane)	Std 0 - 20 ppm 0 - 20 ppm 0 - 20 ppm 0 - 20 ppm 0 - 20 ppm	≤ ±2%	0.1 ppm	6810866		■
Phosphine High Conc. (PH ₃) XXS HC	0 - 1,000 ppm	≤ ±2%	1 ppm	6812020		
Sulfur Dioxide (SO ₂) XXS	0 - 100 ppm	≤ ±2%	0.1 ppm	6810885		■

Pac® 8500	X-am® 5100	X-am® 2800	X-am® 5800	X-am® 8000	Warranty	Recomm. Cal Interval (months)	Max. Cal Interval (months)	Calibration manually or with CC-Vision	Bump Test or Calibration with X-dock®	Comments*
		■	■	■	1-Yr	3	6	5 or 10 ppm NO ₂	5 or 10 ppm NO ₂	
			■	■	1-Yr	3	6	5 ppm NO ₂	5 ppm NO ₂	
			■	■	1-Yr	3	6	25 ppm NO	25 ppm NO	
				■	1-Yr	3	6	10 ppm MeM	10 ppm MeM or 10 ppm THT	MeM available on X-dock® with ≥02.02.11 firmware
			■	■	1-Yr	3	6	10 ppm ETO or 100 ppm CO or 25 ppm Ethylene	10 ppm ETO or 100 ppm CO or 25 ppm Ethylene	Calibration gas capability controlled by sensor code
			■	■	1-Yr	3	6	10 ppm ETO or 100 ppm CO or 25 ppm Ethylene	10 ppm ETO or 100 ppm CO or 25 ppm Ethylene	Calibration gas capability controlled by sensor code
■			■	■	2-Yr	6	12	ambient air 100 ppm CO	ambient air 100 ppm CO	≤19% O ₂ required for bump test of O ₂ on X-dock®
■			■	■	2-Yr	6	12	ambient air 25 ppm H ₂ S	ambient air 25 ppm H ₂ S	≤19% O ₂ required for bump test of O ₂ on X-dock®
		■	■	■	3-Yr	6	12	ambient air	ambient air	≤19% O ₂ required for bump test of O ₂ on X-dock®
			■	■	1-Yr	3	6	ambient air	ambient air	Calibrate at altitude where being used
		■	■	■	2-Yr	6	12	ambient air	ambient air	≤19% O ₂ required for bump test of O ₂ on X-dock Order via configurator
			■	■	1-Yr	3	6	5 ppm NO ₂	5 ppm NO ₂	N ₂ required for zero calibration
			■	■	1-Yr	3	6	2 to 3 ppm COCl ₂	2 to 3 ppm COCl ₂	Calibration gas not sold by Draeger
			■	■	1-Yr	3	6	0.5 ppm PH ₃	0.5 ppm PH ₃	
			■	■	1-Yr	3	6	5 ppm PH ₃	5 ppm PH ₃	Not compatible with CatEx sensor
		■	■	■	2-Yr	3	6	5 ppm SO ₂	5 ppm SO ₂	Do not use H ₂ S/SO ₂ mixed gas on the X-dock®

Sensor Description	Measuring Range	Accuracy (% of measured volume)	Resolution	Part No.	Pac® 60/6500	Pac® 8000
Cat Ex DrägerSensor®						
Cat Ex 125 PR	0 - 100% LEL 0 - 5.0% Vol. 5 - 100% Vol. ^{2,3}	≤ ±1% of LEL	1% LEL 0.1% Vol. 1.0% Vol.	6812950		
Cat Ex 125 PR Mining/Gas (MSHA Approved)	0 - 5.0% Vol. 5 - 100% Vol. ^{2,3}	≤ ±1% of LEL	0.1% Vol. 1.0% Vol.	6813080		
CarEx 125 SR (Shock Resistant)	0 - 100% LEL 0 - 5.0% Vol. 0 - 100% Vol. ⁴	≤ ± 1% LEL at 50 % LEL	1% LEL 0.05% Vol 0.1% Vol	6851900		
IR DrägerSensor®						
Dual IR-Ex/CO ₂ HC	0 - 100%LEL 0 - 100% Vol. 0 - 100% Vol. CO ₂	≤ ±1.5% LEL methane at 50% LEL ≤ ±0.5 Vol.-% CO ₂ at 50 Vol.-%	1% LEL 0.1% Vol. 0.1% Vol.	6800276		
Dual IR-Ex/CO ₂ ES (replaces 6811960)	0 - 100%LEL 0 - 100% Vol. 0 - 5.00% Vol. CO ₂	≤ ±1.5% LEL methane at 50% LEL ≤ ±0.08 Vol.-% CO ₂ at 2.5 Vol.-%	1% LEL 0.1% Vol. 0.02% Vol.	6851880		
IR-Ex ES (replaces 6812180)	0 - 100% LEL 0 - 100% Vol.	≤ ±1.5% LEL methane at 50% LEL	1% LEL 0.1% Vol.	6851881		
IR-CO ₂ ES (replaces 6812190)	0 - 9,900 ppm 0 - 5.00% Vol.	≤ ±0.08 Vol.-% CO ₂ at 2.5 Vol.-%	50 ppm 0.02% Vol.	6851882		
PID DrägerSensor®						
PID HC	0.3 - 2000 ppm	at 100 ppm isobutylene: ≤ ± 2% at zero point: ≤ ± 0.3 ppm isobutylene	0-20 ppm - 100 ppb >20 ppm - 200 ppb >50 ppm - 500 ppb >100 ppm - 1 ppm >200 ppm - 2 ppm >500 ppm - 5 ppm >1000 - 10 ppm	6813475		
PID LC	0-10 ppm isobutylene 0.025-5 ppm ben- zene	at 5 ppm isobutylene: ≤ ± 2% at zero point: ≤ ± 0.05 ppm isobutylene	0-2 ppm - 10 ppb >2 ppm - 20 ppb >5 ppm - 50 ppb	6813500		

* Comments - FKM tubing is recommended for all sensors with the exception of chlorine, nitrogen dioxide and ammonia. For chlorine, use the Teflon-lined Tygon® tubing and for nitrogen dioxide and ammonia use the Tygon® tubing.

1. From December 1st, 2018, 5-year warranty when sold as installed in an X-am® multi-gas monitor. 3-year for replacement sensors.
2. 0-100%Vol range in X-am® 5000 only when selected
3. Full Range mode in X-am® 8000
4. Full Range mode in X-am® 5800





Pac® 8500	X-am® 5100	X-am® 2800	X-am® 5800	X-am® 8000	Warranty	Recomm. Cal Interval (months)	Max. Cal Interval (months)	Calibration manually or with CC-Vision	Bump Test or Calibration with X-dock®	Comments*
				■	3-Yr	3	6	50% LEL CH ₄	50% LEL CH ₄	
				■	3-Yr	3	6	2.5% Vol CH ₄	2.5% Vol CH ₄	“ch4L” mode in X-am® 8000 for 50 to 50,000 ppm range for Method 21 type testing
		■	■		3-Yr	3	6	2.5% Vol CH ₄	2.5% Vol CH ₄	
				■	5-Yr	6	12	50% LEL CH ₄ 50% Vol CH ₄ 50% Vol CO ₂	50% LEL CH ₄ 50% Vol CH ₄ 50% Vol CO ₂	X-am® 8000 Only - Must be installed in HPP 1 - No PID sensor can be installed at the same time.
				■	5-Yr	6	12	50% LEL CH ₄ 50% Vol CH ₄ 2.5% Vol CO ₂	50% LEL CH ₄ 50% Vol CH ₄ 2.5% Vol CO ₂	N ₂ required for CO ₂ zero calibration 0 - 9,900 ppm in X-am® 5600 0 - 50,000 ppm range in X-am 8000
				■	5-Yr	6	12	50% LEL CH ₄	50% LEL CH ₄	Can be configured for 2 ranges/gases via CC-Vision
				■	5-Yr	6	12	2.5% Vol CO ₂	2.5% Vol CO ₂	N ₂ required for CO ₂ zero calibration 0 - 50,000 ppm range in X-am® 8000
				■	1-Yr	1	12	100 ppm isobutylene	100 ppm isobutylene	Use with benzene scrubber tube for benzene specific readings up to 100 ppm (01/2021).
				■	1-Yr	Each use	N/A	5 ppm isobutylene	5 ppm isobutylene	Requires zero air or N ₂ for zero calibration. 30 minute warm up time, if not stored on charger. Use with benzene scrubber tube for benzene specific readings up to 100 ppm (01/2021).

Sensors

Part No.	Sensor
6813500	 DrägerSensor PID-LC ppb (0.03 – 10 ppm isobutylene)
6813475	 DrägerSensor PID-HC (0-2000 ppm isobutylene)
6812950	 DrägerSensor CatEx 125 PR 0-100 % LEL or 0-100 % by vol. CH ₄
6813080	 DrägerSensor CatEx 125 PR- Gas 0-100 % LEL or 0-100 % by vol. CH ₄
6851880	 DrägerSensor Dual IR Ex/CO₂ ES 0 – 100 % by vol. CH ₄ 0 – 100 % LEL 0 – 5 % by vol. CO ₂
6851881	 DrägerSensor IR Ex ES 0 – 100 % by vol. CH ₄ 0 – 100 % LEL
6851882	 DrägerSensor IR CO₂ ES 0 – 5 % by vol. CO ₂
6851900	 DrägerSensor CatEx 125 SR 0-100 % LEL or 0-100 % by vol.
6800276	 DrägerSensor Dual IR Ex/CO₂ HC 0 – 100 % by vol. CH ₄ 0 – 100 % LEL 0 – 100 % by vol. CO ₂
6810881	 DrägerSensor XXS O₂ 0 – 25 % by vol. O ₂
6800530	 DrägerSensor XXS O₂ PR 0 – 30 % by Vol. O ₂

Part No.	Sensor
6812385	 DrägerSensor XXS O₂100 0 – 100 % by vol. O ₂
6812010	 DrägerSensor XXS CO HC 0 – 10000 ppm CO
6813210	 DrägerSensor XXS CO LC 0 – 2000 ppm
6811950	 DrägerSensor XXS CO H₂- CP 0-2000 ppm CO (hydrogen compensated)
6810889	 DrägerSensor XXS CO₂ 0 – 5 % by vol. CO ₂
6811525	 DrägerSensor XXS H₂S LC 0- 100 ppm H ₂ S
6812015	 DrägerSensor XXS H₂S HC 0 – 1000 ppm H ₂ S
6810888	 DrägerSensor XXS NH₃ 0 – 300 ppm NH ₃
6810890	 DrägerSensor XXS Cl₂ 0 – 20 ppm Cl ₂
6810887	 DrägerSensor XXS HCN 0 – 50 ppm HCN
6813165	 DrägerSensor XXS HCN PC 0 – 50 ppm HCN

Part No.	Sensor
6811545	 DrägerSensor XXS NO 0 – 200 ppm NO
6810884	 DrägerSensor XXS NO₂ 0 – 50 ppm NO ₂
6812600	 DrägerSensor XXS NO₂ LC 0 – 50 ppm NO ₂
6810886	 DrägerSensor XXS PH₃ 0 – 20 ppm PH ₃
6812020	 DrägerSensor XXS PH₃ HC 0 – 2000 ppm PH ₃
6810885	 DrägerSensor XXS SO₂* 0 – 100 ppm SO ₂
6811530	 DrägerSensor XXS OV 0 – 200 ppm EO
6811535	 DrägerSensor XXS OV-A 0 – 200 ppm EO
6812025	 DrägerSensor XXS H₂ HC 0 – 4 % by vol. H ₂
6812370	 DrägerSensor XXS H₂ 0 – 2000 ppm H ₂
6812535	 DrägerSensor XXS Odorant 0 – 40 ppm THT

Part No.	Sensor
6811540	 DrägerSensor XXS Ozone 0 – 10 ppm O ₃
6813275	 DrägerSensor XXS CO LC / O₂ 0 – 2000 ppm CO 0 – 25 % by vol. O ₂
6813280	 DrägerSensor XXS CO LC / H₂S LC 0 – 2000 ppm CO 0 – 100 ppm H ₂ S
6814137	 DrägerSensor XXS O₂ / H₂S LC 0 – 25 % by vol. O ₂ 0 – 100 ppm H ₂ S

*If you are using this sensor with H₂S, you will need a KX filter (part no. 6811344) over the sensor.

Not all products, features, or services are for sale in all countries. Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

Corporate Headquarters

Drägerwerk AG & Co. KGaA
Moislinger Allee 53-55
23558 Lübeck, Germany

www.draeger.com

USA

Dräger, Inc.
7256 S. Sam Houston Parkway W.,
Suite 100
Houston, TX 77085
☎ 1 800 4DRAGER
(1 800 437 2437)

Canada

Dräger Safety Canada, Ltd.
2425 Skymark Ave., Unit 1
Mississauga, Ontario L4W 4Y6
☎ 1 877 DRAGER1
(1 877 372 4371)



Locate your Regional Sales
Representative at:
www.draeger.com/contact