

PRODUCT FACT SHEET

E-SPOT® LITEBOX® // E-SPOT® FIREBOX® RECHARGEABLE LANTERN

DESCRIPTION: The E-Spot® is an industrial-duty, rechargeable, portable lantern featuring the latest in power LED technology for

high brightness, long run time and high reliability. The E-Spot® uses three (3) LEDs and deep-dish parabolic reflectors to produce a large spot pattern. Jumper selectable high or low settings to allow for selection of more

light output or more run time. Available in LiteBox®, FireBox® and Power Failure models.

CASE MATERIAL: High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle.

DIMENSIONS: Height: 7 in. (17.8 cm) Length: 11.5 in. (29.2 cm) Width: 5.1 in. (13 cm)

WEIGHT: 7.9 lbs (3.58 kg) with battery (included)

LENS: Unbreakable polycarbonate with scratch-resistant coating

LIGHT SOURCE: Three (3) white high-power LEDs, impervious to shock with a 50,000-hour lifetime

See chart. Three (3) deep-dish parabolic reflectors produce a uniform spot pattern. Optimized electronics provide **LIGHT OUTPUT:**

regulated intensity. Jumper selectable high or low settings.

Zero-maintenance 6V, 12Ah sealed lead acid is rechargeable up to 500 times **BATTERY:**

Red and green indicator LEDs provide charge status

RUN TIME: See chart. Jumper selectable high or low settings.

()

FEATURES: IPX4-rated for weather-resistant operation LED Solid State circuitry provides regulated light output throughout battery life

> Serialized for positive identification Fits existing Streamlight LiteBox® chargers

MODELS: Standard E-Spot® LiteBox® System: Push-button switch. Available in international safety orange or high-visibility

yellow; includes shoulder strap, AC and DC charge cords and charge rack.

Vehicle Mount E-Spot® LiteBox® System: Push-button switch. Available in international safety orange or highvisibility yellow; includes shoulder strap and vehicle-mountable hard-wire rack.

Power Failure E-Spot® LiteBox® System: Push-button switch and "smart" power failure circuitry that automatically goes on when the power goes off. Available in international safety orange or beige; includes AC and DC charge cords and charge rack.

Standard E-Spot® FireBox® System: Toggle switch and two (2) user-programmable ultra-bright blue tail-light LEDs. Available in international safety orange or high-visibility yellow; includes shoulder strap, AC and DC charge cords and charge rack.

Vehicle Mount E-Spot® FireBox® System: Toggle switch and two (2) user-programmable ultra-bright blue tail-light LEDs. Available in international safety orange or high-visibility yellow; includes shoulder strap and vehiclemountable hard-wire charge rack.

APPROVALS*: CE K Most models meet applicable European Community Directives

Charge rack meets requirements of NFPA 1901-14.1.11.2 (2016) mounted in any position

Streamlight's Limited Lifetime Warranty **WARRANTY:**

OPTIONAL 100V, 120V, 230V or 240V AC (home) and 12VDC (automobile) charge cords, hands-free shoulder strap (included

ACCESSORIES: with standard + VM models), locking charge rack, quick-release shoulder/waist strap

OUTPUT **RUNTIME**

540 330 LUMENS LUMENS 7h 15h 469m 358m 55,000 cd 32000 cd

E-SPOT LITEBOX PERFORMANCE CURVE HIGH OUTPUT REGULATED RUNTIME LOW OUTPUT REGULATED RUNTIME

INTENSITY

DISTANCE

All performance claims to ANSI/NEMA FL1-2019 Standard

Issued: 04/01/10

Revised: 08/04/22 Assembled in the USA. Rev: 1 Document #198

^{*}See product for specific ratings.